

The Vista DS[™] fixed window system is engineered to beautifully complement our innovative door systems. Designed from the ground up based on feedback from our popular Vista Wall product, Vista DS[™] offers some of the thinnest profiles for either fixed or operable fenestration products (just 1 1/4") – providing a sleek, modern appearance. It also boasts expansive height and width dimensions, maximizing the glass-to-frame ratio that enhances natural light and delivers unobstructed views.

FL46965






PANEL MINIMUM / MAXIMUM


Min Panel Width: 18" Min Panel Height: 18"

Max Panel Width: 108" Max Panel Height: 168"




OVERVIEW DIAGRAM





Exterior Front Elevation


Vertical Cross Section




Top Down Cross Section
Exterior Assembly
(interior assembly on next page)



Top Down Cross Section Interior Assembly










GLAZING DETAILS





FINISH OPTIONS

Standard Finishes









Wood clad veneer option shown

Standard Wood Finishes





Silver













Sapele **Faux Wood Grain Finishes**



Cherry





Walnut





Pine



Red




Walnut Brown

NOTE: All Interior wood clad veneer products should be properly finished or sealed within 36 hours of delivery or stored in a climate controlled space until it can be properly finished or sealed.

GRID OPTIONS







3/4" FLAT MUNTIN E0068


NOTE: The 3/4" flat muntin is primarily used for sliding doors, however if your project has folding and sliding doors this muntin will be used to make them all match.

NOTE: Additional muntin, kickplate, and midrail options available upon request.




CONFIGURATIONS

SINGLE UNIT



MULTIPLE UNITS





DESIGN PRESSURE CHARTS

DESIGN PRESSURE CHART (SINGLE UNIT)

HVHZ, WZ3, & Non-Impact

Panel Width

| | 36 | 42 | 48 | 54 | 60 | 66 | 72 | 78 | 84 | 90 | 96 | 102 | 108 |
|-----|----|----|----|----|----|------|------|------|------|------|------|------|------|
| 78 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 |
| 84 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 50 | 50 | 50 | |
| 90 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | 46.7 | | |
| 96 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | | | |
| 102 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | | | | |
| 108 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | | | | | |
| 114 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 120 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 126 | 70 | 70 | 70 | 70 | 70 | 63.6 | | | | | | | |
| 132 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 138 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 144 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 150 | 70 | 70 | 70 | 70 | | | | | | | | | |
| 156 | 70 | 70 | 70 | 70 | | | | | | | | | |
| 162 | 70 | 70 | 70 | | | | | | | | | | |
| 168 | 70 | 70 | 70 | | | | | | | | | | |

DESIGN PRESSURE CHART (MULTIPLE UNITS)

HVHZ

Panel Width

| | 36 | 42 | 48 | 54 | 60 | 66 | 72 | 78 | 84 | 90 | 96 | 102 | 108 |
|-----|----|----|----|----|----|------|------|------|------|------|------|------|------|
| 78 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 |
| 84 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 50 | 50 | 50 | |
| 90 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | 46.7 | | |
| 96 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | | | |
| 102 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | | | | |
| 108 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | | | | | |
| 114 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 120 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 126 | 70 | 70 | 70 | 70 | 70 | 63.6 | | | | | | | |
| 132 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 138 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 144 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |

WZ3, & Non-Impact

Panel Width

| | 36 | 42 | 48 | 54 | 60 | 66 | 72 | 78 | 84 | 90 | 96 | 102 | 108 |
|-----|-------------|------|------|------|----|------|------|------|------|------|------|------|------|
| 78 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 | 53.8 |
| 84 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 50 | 50 | 50 | |
| 90 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | 46.7 | | |
| 90 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | 46.7 | | | |
| 10 | 2 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | 50 | | | | |
| 10 | 8 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | 53.8 | | | | | |
| 114 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 12 | 70 | 70 | 70 | 70 | 70 | 63.6 | 58.3 | | | | | | |
| 12 | 6 70 | 70 | 70 | 70 | 70 | 63.6 | | | | | | | |
| 13 | 2 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 13 | 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 14 | 4 70 | 70 | 70 | 70 | 70 | | | | | | | | |
| 15 | 70 | 70 | 70 | 67.6 | | | | | | | | | |
| 15 | 6 70 | 70 | 66.6 | 59.8 | | | | | | | | | |
| 16 | 2 70 | 67.2 | 59.3 | | | | | | | | | | |
| 16 | 8 69.7 | 60.2 | 53.1 | | | | | | | | | | |



TEST PERFORMANCE RESULTS

- Approved for use in Miami-Dade HVHZ Zone
- Florida Building Code Approved Product Approval FL 46965
- Tested for Thermal Requirements
- Air Infiltration: ASTM E283-19

Water Infiltration: ASTM E331-00(23)

• Wind Load: TAS 202-94

■ Large Missile Impact: TAS 201-94

• Cyclic Load: TAS 203-94









EURO-WALL 10 YEAR WARRANTY

Euro-Wall warrants the products to be free from manufacturing defects for a period of 10 years from the date of purchase.

888.989.EURO (3876) W W W . e u r o - w a l l . c o m

MANUFACTURING

2200 Murphy Court North Port, Florida 34289 888.989.3876 • 941.979.5316



SHOWROOM

1211 Stirling Road, Unit 102, Dania Beach, Florida 33004 954.610.2572

Proud Member of the American Architectural Manufacturers Association.

